

TERRAIN TAMER



4WD PRODUCTS

Twin Piston Air Compressor



> **Specifications**

- 75 litres per minute output
- Outstanding performance 40 mins @ 40PSI
- Heavy duty power cord with battery clamps and a 30amp inline fuse
- Stainless steel valves and high performance PTFE piston ring
- Powerful 0.25HP permanent magnet motor draws 15 amps to a maximum of 30amps
- Coil air hose and pressure gauge comes with a solid brass, snap-on fitting to the compressor
- Built-in tyre deflation valve
- Twin compartment carry bag
- Additional fittings in the lid
- Carry bag included

PART NUMBER	DESCRIPTION
TTAC2	TWIN AIR COMPRESSOR

TTAC2 CAPACITY

Maximum air flow	75 litres per minute
Maximum voltage	13.8 volt
Maximum amperage draw	30A
Maximum working pressure	150 PSI
Maximum restart pressure	200 PSI
Maximum ambient temp	60 C
Minimum ambient temp	- 55C
Maximum duty cycle time	40 mins@ 40 PSI @ 24C

TERRAIN TAMER



4WD PRODUCTS

Series 3 Air Compressor



› Specifications

- Easy twist screw-on brass inflator tip
- Quick release 26ft coil hose with gauge
- Heavy duty 8ft power cord with battery clamps
- Rubber anti-vibration feet
- Can be permanently mounted and hard wired if desired
- Includes bonus carry bag
- 160 LPM maximum output
- 150 PSI maximum pressure
- 3 nozzle adapters for inflatables

PART NUMBER	DESCRIPTION
TTAC3	Series 3 AIR COMPRESSOR

TTAC3 CAPACITY

Maximum air flow	160 litres per minute
Maximum voltage	13.8 volt
Maximum amperage draw	45A
Maximum working pressure	120 PSI
Maximum restart pressure	150 PSI
Maximum ambient temp	60C
Minimum ambient temp	-55C